



DB9防尘帽

1	DCD
2	RXD
3	TXD
4	DTR
5	GND
6	DSR
7	RTS
8	CTS
9	RI

DB9/M	DB9/M
1	1
2	2
3	3
4	4
5	5
6	6
7	7
8	8
9	9

直通式A



电气特性:

1. 100%开路、短路、断路测试。
2. 绝缘阻抗: 10M Ohm Min
3. 导通阻抗: 2 Ohm MAX
4. 耐压: DC 300V, 0.01/Sec

NO.		PART NAME	SPEC DESCRIPTION	QTY	UNIT	TOLERANCE		OIKWAN 东莞市嵩群实业有限公司 DONGGUAN AIQUN INDUSTRIAL CO., LTD	
A		INITIAL RELEASE				INCHES		SCALE	
REV		DESCRIPTION OF CHANGE				MM		UNIT	
6		防尘帽	DB9防尘帽	2	pcs	.X	.015	.30	NONE
5		DB公头	DB9/M 镀镍	1	pcs	.XX	.010	.10	MM
4		胶料	LDPE,本色, MOLDED,ROHS	A/R	g	.XXX	.005	.05	1/1
3		胶料	45P PVC, 黑色	A/R	g	DRAWN BY		WSY	CUSTOMER:
2		螺栓	Ø2.3*37mm 镀镍	2	pcs	CHECK BY		DATE	24/12/23
1		线材	9芯圆线 黑色 (AWG28*9C+D+AL OD5.5) PVC外被 裸铜	A/R	mm	CUSTOMER P/N:		DWG NO:	
						TITLE: DB9公-DB9公 短体			
						P/N: ADB11112AQ01			