



DB9防尘帽

1	DCD
2	RXD
3	TXD
4	DTR
5	GND
6	DSR
7	RTS
8	CTS
9	RI

DB9/M	DB9/F
1	1
2	2
3	3
4	4
5	5
6	6
7	7
8	8
9	9

直通式A



电气特性:

- 1.100%开路、短路、断路测试。
- 2.绝缘阻抗: 10M Ohm Min
- 3.导通阻抗: 2 Ohm MAX
- 4.耐压: DC 300V,0.01/Sec

7	防尘帽	DB9防尘帽	2	pcs	A	INITIAL RELEASE			24/12/23
6	螺栓	Ø2.3*37mm 镀镍	2	pcs	REV	DESCRIPTION OF CHANGE			DATE
5	DB公头	DB9/M 镀镍	1	pcs	TOLERANCE INCHES MM			OIKWAN® 东莞市嵩群实业有限公司 DONGGUAN AIQUN INDUSTRIAL CO.,LTD	
4	胶料	LDPE,本色, MOLDED,ROHS	A/R	g	.X	.015	.30		
3	胶料	45P PVC, 黑色	A/R	g	.XX	.010	.10		
2	DB母头	DB9/F 镀镍	1	PCS	.XXX	.005	.05	SCALE	NONE
1	线材	9芯圆线 黑色 (AWG28*9C+D+AL OD5.5) PVC外被 裸铜	A/R	mm	DRAWN BY	WSY		UNIT	MM
NO.	PART NAME	SPEC DESCRIPTION	QTY	UNIT	CHECK BY			SHEET	1/1
					CUSTOMER P/N:			DATE	24/12/23
							DWG NO:		
							TITLE: DB9公-DB9母 短体		
							P/N: ADB12112AQ02		