



电气特性:
 1.100%开路、短路、断路测试。
 2.绝缘阻抗: 10M Ohm Min
 3.导通阻抗: 2 Ohm MAX
 4.耐压: DC 300V,0.01/Sec

NO	NAME	Description	QTY	Unit
6	塑胶	45P PVC, MOLDED, ROHS	A/R	G
5	塑胶	LDPE, 本色, MOLDED, ROHS	A/R	G
4	连接器	USB A/M, PIN 镀金1u, ROHS	1	PCS
3	PCB板	PCBA WITH FT232 CHIP, ROHS	1	PCS
2	连接器	DC3.5公头, 3极, 镀镍	1	PCS
1	线材	28AWG*3C, BARE COPPER, PVC JACKET, ROHS	A/R	M

A	INITIAL RELEASE		25/08/26	
REV	DESCRIPTION OF CHANGE			DATE
TOLERANCE				
INCHES		M/M		
.X	.015	.30		
.XX	.010	.10		
.XXX	.005	.05		
DRAWN BY	TONY CHAN		SCALE	NONE
			UNIT	MM
CHECK BY			SHEET	1/1
			DATE	25/08/26
CUSTOMER. P/N:		P/N: ADC170010002		

OIKWAN 东莞市蔼群实业有限公司
 DONGGUAN OIKWAN INDUSTRIAL CO., LTD.

SCALE NONE
 UNIT MM
 SHEET 1/1
 DATE 25/08/26
 TITLE: USB TO DC3.5
 DWG NO.:
 REV A