


电气特性:

- 1.100%开路、短路、断路测试。
- 2.绝缘阻抗: 10M Ohm Min
- 3.导通阻抗: 2 Ohm MAX
- 4.耐压: DC 300V,0.01/Sec



	P1	P2
VCC	_____	1
RXD	_____	2
TXD	_____	3
GND	_____	5

NO	NAME	Description	QTY	Unit
6	塑胶	45P PVC,MOLDED,ROHS	A/R	G
5	塑胶	LDPE,本色,MOLDED,ROHS	A/R	G
4	连接器	USB A/M, 镀镍	1	PCS
3	PCB板	PCBA WITH FT232+ZT213 CHIP,ROHS	1	PCS
2	连接器	MICRO USB 5P, 镀镍	1	PCS
1	线材	28AWG*4C,BARE COPPER,PVC JACKET,ROHS	A/R	M

A	INITIAL RELEASE		25/08/16	
REV	DESCRIPTION OF CHANGE			DATE
TOLERANCE				
INCHES		M/M		
.X	.015	.30		
.XX	.010	.10		
.XXX	.005	.05		
DRAWN BY	TONY CHAN		SCALE	NONE
			UNIT	MM
CHECK BY			SHEET	1/1
			DATE	25/08/16
CUSTOMER. P/N:		P/N: AMC130010002		

DIKWAN® 东莞市嵩群实业有限公司
DONGGUAN AIQUN INDUSTRIAL CO., LTD.