



电气特性:
 1. 100%开路、短路、断路测试。
 2. 绝缘阻抗: 10M Ohm Min
 3. 导通阻抗: 2 Ohm MAX
 4. 耐压: DC 300V, 0.01/Sec

	P1	P2
VCC	_____	1
RXD	_____	2
TXD	_____	3
GND	_____	5

NO	NAME	Description	QTY	Unit
6	塑胶	45P PVC,MOLDED,ROHS	A/R	G
5	塑胶	LDPE,本色,MOLDED,ROHS	A/R	G
4	连接器	USB A/M,PIN 镀镍	1	PCS
3	PCB板	PCBA WITH FT232+ZT213 CHIP,ROHS	1	PCS
2	连接器	MINI USB 5P,镀镍	1	PCS
1	线材	28AWG*3C,BARE COPPER,PVC JACKET,ROHS	A/R	M

A	INITIAL RELEASE		25/08/16	
REV	DESCRIPTION OF CHANGE			DATE
TOLERANCE				
INCHES		M/M		
.X	.015	.30		
.XX	.010	.10		
.XXX	.005	.05		
DRAWN BY	TONY CHAN		SCALE	NONE
			UNIT	MM
CHECK BY			SHEET	1/1
			DATE	25/08/16
CUSTOMER. P/N:		P/N: AMN150010002		

DIKWAN® 东莞市嵩群实业有限公司
 DONGGUAN AIQUN INDUSTRIAL CO., LTD.